

Specifications

Construction Yarn Composition Pile Weight Total Weight Pile Height **Total Thickness** Gauge Plank size Primary Backing Secondary Backing

3/4/6mm high-low tip sheared loop pile BCF PP / Air-Entangled PP ca. 880g/m² (26 oz/y²) ca. 3446g/m² (102 oz/y²) ca. 3mm / 5mm ca. 8mm 1/12" 25cm x 100cm Non-Woven EcoBacking 20pcs per Box

4 Boxes per Pallet Layer x 7 Layers (140m²)

Warranties

Packing

Lifetime Limited Carpet Wear Warranty Lifetime Static Warranty

Ideal for Medium Commercial Use

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing.

Where seaming is necessary, a seam sealant must be used for all such installations. Due to dyelot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Performance (as tested by ITTS Inc. USA)

Stain Resistance Static Control Tuft Bind **Dimensional Stability** Flammability

Radiant Panel Pill Test Smoke Density

Colourfastness to light to wet & dry crocking to ozone

9 (AATCC-175-2003) Less < 4 KV (AATCC 134-1996) 8.0 lbs (ASTM-D-1335) < 0.1% change (AACHEN)

>= 0.35 watts/cm² (ASTM-E-648-06) 8 (ASTM-D-2859-06) Max 450 (ASTM-E-662-06)

5 (AATCC-16E) 5 (AATCC-165) 5 (AATCC-129)

Suitability

Magical Tiles is an extremely affordable yet strong and durable carpet tile that fully meets the needs of today's competitive office environment.

Due to the cut & loop texture and the solid colorations of Magical Tile, the edge lines may be visible if planks of the same color are joined next to each other. The visible edge lines are an inherent characteristic of the plank and not a defect, just as one can also see the edge lines when joining wood planks or PVC

If the visual effect of the edge lines is required to be minimised, we recommend to install planks of different and contrasting colors next to each other, as can be seen in our illustrations.



Mag 1C3





















