



1. Storage
 - a. Store the tiles in a dry, clean space with a normal temperature of below 40C
 - b. Keep the tile atleast 2 mts away from heat producers, such as boilers, fire places etc
 - c. Keep the tiles in normal temperature for 24hrs before installation
2. Installation & Adhesive
 - a. Conditions on site as per BS 8203
 - b. It is important to have proper floor levelling prior to installation of tiles
 - c. Any multi-purpose adhesive, with full glue down is recommended
3. Cleaning & Maintenance
 - a. Placing ground mat in the doorway is important
 - b. Regular mopping and usage of mild detergent is recommended
 - c. Waxing and polishing is not required. Spray Buff for enhanced finish

TEST ITEM	UNIT	METHOD	MDL	SPEC.	RESULT	CONCL	General Specifications
HEAVY METAL (ASTM F963)	---	---	---	---	---	---	2.0mm (T) x 152mm (W) x 915mm (L) x 0.15mm W/L
CADMIUM	ppm	ASTM F963	1	< 75.0	n.d.	PASS	2.0mm (T) x 6" (W) x 36" (L) x 0.15mm W/L
LEAD	ppm	ASTM F963	1	< 90.0	n.d.	PASS	Packaging
MERCURY	ppm	ASTM F963	2	< 60.0	n.d.	PASS	24 pcs / box (3.343 / sqm)
ARSENIC	ppm	ASTM F963	1	< 25.0	n.d.	PASS	Usage
CHROMIUM	ppm	ASTM F963	1	< 60.0	n.d.	PASS	Commercial and Heavy Duty Traffic
BARIIUM	ppm	ASTM F963	1	< 1000	n.d.	PASS	Weight per box
ANTIMONY	ppm	ASTM F963	2	< 60.0	n.d.	PASS	8.68 kgs / per box
SELENIUM	ppm	ASTM F963	2	< 500	n.d.	PASS	
TOTAL LEAD	ppm	USEPA 3052	2	< 600	61.5	PASS	



Luxury Vinyl Tiles
Commercial Real Wood Tile Collection in 2mm



AVB-9881



AVB-9882



AVB-9631



AVB-9243



AVB-9887

General Specifications : 2.0mm (T) x 152mm (W) x 915mm (L) x 0.15mm W/L
Packaging : 24 pcs / box (3.343 / sqm)



AVB-9635



AVB-9279



AVB-9521



AVB-9315



AVB-9041



AVB-9401

General Specifications : 2.0mm (T) x 152mm (W) x 915mm (L) x 0.15mm W/L
Packaging : 24 pcs / box (3.343 / sqm)