

Traffic 2

CARPET TILES



Quarter-Turn
Only



Quarter-Turn
Only



2401 FREEZER RED



2402 JELLO BLUE



2404 PURPLE FUZZ



2405 APPLE GREEN



2406 ROYAL GOLD



2409 ORANGE SUN




2507 GREY MINE



2508 COFFEE CLUB




2509 BLUISH GREY



2510 DARK GREY



2405 APPLE GREEN
2508 COFFEE CLUB



Quarter-Turn
Only

Traffic 2 Specifications

Construction	1/10" Level Loop Pile
Yarn Composition	100% Nylon
Pile Weight	ca. 576 g/m ² (17 oz/yd ²) (+/- 10%)
Total Weight	ca. 3500 g/m ² (103 oz/yd ²)
Pile Height	ca. 3 mm (+/- 0.5 mm)
Total Height	ca. 5 mm (+/- 0.5 mm)
Stitch Rate	11 per inch
Density	6096
Backing	ECO Backing with Fibre Glass Layer (PVC-Free Tile)
Size	50 cm x 50 cm
Packing	20 pcs per box (5 m ²)

Performance (as tested by ITTS Inc. USA)

Static Control	Pass - Max. 4 kV (AATCC-134-1996)
Tuft Bind	Pass - 11.4 lbs (ASTM-D-1335)
Dimensional Stability	Pass - Max. 2.4% change (AACHEN)
Indoor Air Quality (V.O.C.)	Pass - No VOC Detected (ASTM-D5116-10)
Flammability	
Radiant Panel	Pass - Class I (ASTM-E-648-10)
Pill Test	Pass - 8 (ASTM-D-2859-96)
Smoke Density	Pass - Max. 450 (ASTM-E-662-06)
Colourfastness	
to light	Excellent - 5 (AATCC-16E)
to wet & dry crocking	Excellent - 5 (AATCC-165)
to ozone	Excellent - 5 (AATCC-129)

Suitability

Traffic 2 Tile is an extremely affordable yet strong and durable carpet tile that fully meets the needs of today's competitive office environment.

Due to the cut & loop texture and the solid colorations of Traffic 2 Tile, the edge lines may be visible if planks of the same color are joined next to each other. The visible edge lines are an inherent characteristic of the plank and not a defect, just as one can also see the edge lines when joining wood planks or PVC planks.

If the visual effect of the edge lines is required to be minimised, we recommend to install planks of different and contrasting colors next to each other, as can be seen in our illustrations.

Warranties

15 Year Carpet Wear Warranty
Lifetime Anti-shock Carpet Warranty

Ideal for Heavy Contract Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. The seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles. Due to dye lot variations, actual colour may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Environment

The design and production of Traffic 2 Tile conforms to the ISO 14001:2004 Environmental Management System and complies with environmental regulations.

As a responsible manufacturer and to minimize our carbon footprint, a majority of our excess production materials are recycled in-house resulting in a minimum of 10% recycled content in our tile backing. Traffic 2 Tile does not contain any PVC in its manufactured materials and packaging.

Traffic 2 Tile is an environmentally friendly "green" carpet.

Installation Method



Quarter-Turn
Only

