







**404A NATURAL GREEN** 

## LUXURY GRASS CARPET Specifications

Construction Yarn Composition

Pile Weight Total Weight Pile Height Total Height Tuft Density Yarn Density Cohesion Base Roll Width Roll Length 3/8" Tufted Cut Pile 100% Synthetic (Blend of Polypropylene and Polyetheylene) with U/V Stabilizer Ca. 2000 g/m<sup>2</sup> (59 oz/yd<sup>2</sup>) Ca. 3000 g/m<sup>2</sup> (85 oz/yd<sup>2</sup>) Ca. 40 mm (+/- 10%) Ca. 43 mm (+/- 10%) 18,900 d/m<sup>2</sup> 12,500 Draining Latex 2 m 25 m

## Performance (as tested by ITTS Inc. USA)

100% Solution Dyed	Extremely Hardwearing, Waterproof and Abrasion Resistant Fibre.
Synthetic Draining Latex	Mildew Proof, Rot Proof, Excellent Dimensional Stability, Most Suitable for
U/V Stabilized	Outdoor Use and for all Types of Weather. Chemically Treated to provide maximum protection against fading from ultraviolet sunlight.
Solution Dyed	For Excellent Colourfastness

## **Warranties**

5 Year Carpet Residential Wear Warranty 3 Year Colourfastness Warranty Lifetime Antishock Carpet Warranty

Ideal for Swimming Pool Borders, Landscape Decoration, Exhibitions, Displays, Outdoor uses, Nautical uses.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant **must** be used for all such installations. Due to dyelot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.







