8819 Exotic Oak

SpecificationsSuface FinishRegistered Emboss (EIR),
V-Grooved EdgeDimension (L x W x T)1218mm x 196mm x 12mmConstructionHigh Density Fiber Board (HDF)Wear Layer58 GSMDécor PaperUV Resistant, Level 6Locking SystemVälinge 2G Locking SystemPacking (pcs/Box)5 pcs/Box (1.193sqm)





Performance Tests

CHARACTERISTIC	REQUIREMENT	RESULT
Abrasion Resistance	AC4	ABRASION CLASS: AC4-32
Impact Resistance	IC2	IMPACT CLASS
Stain Resistance	5	GRADE 5: No Visible change to surface
Resistance to Cigarette	≥ Grade 4	GRADE 4: Cigarette ember no visible changes to surface
Effect of Furniture Leg	No Damage shall be visible when tested with foot type O	No visible damage accoding to EN424
Effect of Castor Chair	No change or damage as per EN425	No visible change or damage
Thickness Swelling	<u>≤</u> 18%	≤ 8%
Light Fastness	Blue Wool Scale,not worse than 6 Grey Scale, not worse than 4	Blue Wool: ≥ 6 Grey Scale: ≥ 4
Porosity	Graphite Test 1	Grade 4-5, No visible effect
Fire Resistance	As per DIN 4102	Ignites with diffuculty, BMC B1
Indentation Test	As per DIN 51955	Residual indentation 0.0mm
Susceptibility To Cracks	As per EN 438.2.26	No cracks observable

Our patented mechanical locking system makes professional quality installation as easy as;

LOCK





Edge of nk into Channel





Elegance & Comfort in Modern Living





Wood



-

8599 Winter White Oak







Design Name: Regensberg Design No.: 8819 Nigerian Oak Surface Finish: Registered Emboss